



FLUORESCENT LUMINAIRES

T8 Recess Open Type (M Bar)




- Made of high quality cold-rolled steel housing of thickness 0.6 mm.
- Five-stage zinc phosphate pretreatment for rust resistance.
- Finished with white polyester powder by two-stage electrostatic method.
- Heavy duty spring -locked type lamp holder G13
- Cable THW 0.5 sq.mm. 105°C (TIS.11-1988 STANDARD)
- 99.85% high purity anodized aluminium reflector with Total Reflectance of 87% (87) for normal usage. Optional : Total Reflectance of 95% (95) for high efficiency pupose.



INSTALLATION & APPLICATION

- For recessed M-bar ceiling installation.
- Application : Office , Meeting Room.



MODEL	Watts	Size	Dimension				
			W1	W2	L1(R/S)	L2(R/S)	H1(R/S)
CL-RL-02M-O-12-118-(R/S)	1 x FL T8 (S)	1' x 2'	270	296	610/ 635	636/ 661	85/ 105
CL-RL-02M-O-12-218-(R/S)	2 x FL T8 (S)	1' x 2'	270	296	610/ 635	636/ 661	85/ 105
CL-RL-02M-O-22-218-(R/S)	2 x FL T8 (S)	2' x 2'	570	596	610/ 635	636/ 661	85/ 105
CL-RL-02M-O-22-318-(R/S)	3 x FL T8 (S)	2' x 2'	570	596	610/ 635	636/ 661	85/ 105
CL-RL-02M-O-22-418-(R/S)	4 x FL T8 (S)	2' x 2'	570	596	610/ 635	636/ 661	85/ 105
CL-RL-02M-O-14-136-(R/S)	1 x FL T8 (L)	1' x 4'	270	296	1220/ 1245	1246/ 1271	85/ 105
CL-RL-02M-O-14-236-(R/S)	2 x FL T8 (L)	1' x 4'	270	296	1220/ 1245	1246/ 1271	85/ 105
CL-RL-02M-O-24-236-(R/S)	2 x FL T8 (L)	2' x 4'	570	596	1220/ 1245	1246/ 1271	85/ 105
CL-RL-02M-O-24-336-(R/S)	3 x FL T8 (L)	2' x 4'	570	596	1220/ 1245	1246/ 1271	85/ 105
CL-RL-02M-O-24-436-(R/S)	4 x FL T8 (L)	2' x 4'	570	596	1220/ 1245	1246/ 1271	85/ 105

* (S) = Short Lamp (600 mm.) , (L) = Long Lamp (1200 mm.)