



# FLUORESCENT LUMINAIRES

## T8 Surface Mounted Open Type

CL-SL-02-0





- Made of high quality cold-rolled steel housing of thickness 0.6 mm.
- Five-stage zinc phosphate pretreatment for rust resistance.
- Finished with white polyester powder by two-stage electrostatic method.
- Heavy duty spring -locked type lamp holder G13
- Cable THW 0.5 sq.mm. 105°C (TIS.11-1988 STANDARD)
- 99.85% high purity anodized aluminium reflector with Total Reflectance of 87% (87) for normal usage. Optional : Total Reflectance of 95% (95) for high efficiency pupose.



### INSTALLATION & APPLICATION

- For surface mounted or suspension rod installation.
- Application : Office , Meeting Room.



MODEL	Watts	Size	Dimension		
			W1	L1(R/S)	H1
CL-RL-02T-O-12-118-(R/S)	1 x FL T8 (S)	1' x 2'	300	610/ 635	100
CL-RL-02T-O-12-218-(R/S)	2 x FL T8 (S)	1' x 2'	300	610/ 635	100
CL-RL-02T-O-22-218-(R/S)	2 x FL T8 (S)	2' x 2'	600	610/ 635	100
CL-RL-02T-O-22-318-(R/S)	3 x FL T8 (S)	2' x 2'	600	610/ 635	100
CL-RL-02T-O-22-418-(R/S)	4 x FL T8 (S)	2' x 2'	600	610/ 635	100
CL-RL-02T-O-14-136-(R/S)	1 x FL T8 (L)	1' x 4'	300	1220/ 1245	100
CL-RL-02T-O-14-236-(R/S)	2 x FL T8 (L)	1' x 4'	300	1220/ 1245	100
CL-RL-02T-O-24-236-(R/S)	2 x FL T8 (L)	2' x 4'	600	1220/ 1245	100
CL-RL-02T-O-24-336-(R/S)	3 x FL T8 (L)	2' x 4'	600	1220/ 1245	100
CL-RL-02T-O-24-436-(R/S)	4 x FL T8 (L)	2' x 4'	600	1220/ 1245	100

\* (S) = Short Lamp (600 mm.) , (L) = Long Lamp (1200 mm.)