





# FLUORESCENT LUMINAIRES

## T8 & T5 Weather Proof (IP65)



**PEP-T8/T5**

- Injected polycarbonate (PC) in grey color with injection molded clear prismatic UV
- stabilized polycarbonate (PC) with curved to anti-glare.
- Cold-rolled steel plate, finished with high glossy baked white polyester powder coating
- Rotary-locked type lamp holder G13 (TIS.344-1987 STANDARD)
- Rotary-locked type starter holder G13 (TIS.344-1987 STANDARD)
- Stainless clip lock. (SL)
- Cable THW 0.5 sq.mm. 105°C (TIS.11-1988 STANDARD)



MODEL	Type	Dimension			Remark
		L	W	H	
PEP-T8-118-WR/SL	1 x FL T8 (S)	670	110	108	
PEP-T8-218-WR/SL	2 x FL T8 (S)	670	170	108	
PEP-T8-136-WR/SL	1 x FL T8 (L)	1270	110	108	
PEP-T8-236-WR/SL	2 x FL T8 (L)	1270	170	108	
PEP-T5-114-WR/SL	1 x FL T5 (S)	610	60	80	
PEP-T5-214-WR/SL	2 x FL T5 (S)	610	100	80	
PEP-T5-128-WR/SL	1 x FL T5 (L)	1210	60	80	
PEP-T5-228-WR/SL	2 x FL T5 (L)	1210	100	80	

\* (S) = Short Lamp (600 mm.) , (L) = Long Lamp (1200 mm.)